

TEL: +46 070-536 3939 WEB: www.kelberg.se



KEL-BERG 4-AXLE 38T DRAWBAR TIPPER 30 M³ HARDOX

WEIGHTS & MEASURES:

Total length 13,380 / 15,080 / 15,600 mm Drawbar length 3,200 / 4,900 / 5,400 mm

Front overhang 770 mm
Rear overhang 1,350 mm
Coupling height 650 mm
Width 2,550 mm

Axle distance 1,310 / 4,940 / 1,810 mm

TRAILER DIMENSIONS:

Internal length 8,900 mm
Internal width 2,440 mm
Height inside 1,350 mm

Cubic Capacity 30

Tipping angle 46 degrees

Speed 90 km/h
Front axle pressure 18,000 kg
Rear axle load 20,000 kg
Total weight 38,000 kg
Service weight 7,950 kg

CHASSIS:

Made of heavy duty main frame, welded steel construction with Trako pulls.













PAGE: 2

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER 30 M³ HARDOX

BODY:

Hardox steel body
Approximately 30 m³
8 mm bottom
6 mm sides
Tipping cylinder Penta - MAX 170 Bar

AXLES:

2 x 9ton BPW axles with front disc brakes 2 x 10ton BPW axles with rear disc brakes Front and rear air suspension with level valve control. With ABS, EBS 4th axle liftable, manoeuvrable from cab (Pin 10)

WHEELS:

8pcs 385/65R22.5 mounted on Aluminium Alcoa Dura-bright rims M+S

BRAKING:

2-circuit compressed air system with EBS and ABS, Spring brake bells for the parking brake

ELECTRICAL SYSTEM:

24 Volts according to current regulations3 x 3 multi-chamber rear lights6 LED work lights2 work lights in the tipping bucket













PAGE: 3

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER 30 M³ HARDOX

ELECTRICAL CONNECTORS:

1 x 14-pin connector for lighting

PAINTING:

Chassis colour: RAL Colour of tipper box:

OTHER:

Rear reflective signs (ECE70)
Red/white contour markings sides and rear
Fenders with anti-spray
2 pcs weight clocks
2 rear flashing lights - active with reverse light
1 large Kelberg rear mudguard.
Plastic on rear underrun
Spring on tie rod

COSTED OPTIONAL EXTRAS:

Flip top pneumatic canopy With remote control Colour of canopy Plastic bottom and sides













PAGE: 4

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER 30 M³ HARDOX













PAGE: 5