



MODEL
T250K

KEL-BERG 3-AXLE 30 M³ HARDDOX
TIPPING TRAILER

SPECIFICATION FOR T250K

KEL-BERG 3-AXLE 30 M³ HARDOX TIPPING TRAILER

WEIGHTS & DIMENSIONS:

Overall length	9,820 mm
Coupling height	1,250 mm
Width	2,550 mm
King-pin - 2nd axle	5,750 mm (7,750 extended position)
Centre distance	1,360 mm / 1,360 mm

DIMENSIONS OF TIPPING BODY:

Internal length	7,900 mm
Internal width	2,300 mm
Internal height	1,450 mm

Speed	90 km/h
King-pin load	18,000 kg
Rear axle load	27,000 kg
Total weight	45,000 kg

CHASSIS:

Made with heavy-duty main frame, welded steel construction.

TIPPING BODY:

8mm bottom
6mm side
HD 450 HARDOX

WHEELS & TYRES:

6 pcs 385/65R22.5 mounted on steel rim



SPECIFICATION FOR T250K

KEL-BERG 3-AXLE 30 M³ HARDOX TIPPING TRAILER

AXLES:

3 x 9 tonne BPW axles with drum brakes
1st axle liftable, runs automatically
Air suspension with level valve manoeuvrable
With ABS, EBS

BRAKES:

2-circuit compressed air system with EBS and ABS,
Spring brake bells for parking brake
1 pc air Duomatic

ELECTRICAL SYSTEM:

24 Volts according to current regulations
2 x multi-chamber rear lights
Diode type side/position lights
2 x Halogen rear lights at the rear

ELECTRICAL CONNECTORS:

1 x 14 pole plug for lighting

PAINTING:

3 coats of base paint with zinc primer
2 component surface coating
Colour: Any RAL colour



SPECIFICATION FOR T250K

KEL-BERG 3-AXLE 30 M³ HARDOX TIPPING TRAILER

OTHER:

Red reflective plates (ECE70) at the rear

White reflective (ECE104) contour markings on sides and rear

Fenders with anti-spray

